



AWG Turbo Twist

All you need!



You don't
choose the fire...

...you choose how
to put it out!

- Tip 250 Series
- Tip 125 Series
- CAFS
- Fire-Ex

- Piercing
- High Exp. Foam
- Foam Agent Tip
- Low Exp. Foam

- Smooth Bore
- Container Fog
- Fog
- Flat Stream

AWG Fittings, LLC

Phone: 508 850 5260

Fax: 508 850 5262

info@awg-fire.com

www.awg-fire.com



AWG Turbo Twist Series

The Turbo Twist nozzle from AWG Fittings, LLC offers multiple interchangeable tips, for endless applications. The quick connection system takes only seconds to change the tips and locks into place to prevent unintentional breaking apart. It is compatible with both water and foam, for special applications. The rugged aluminum nozzle is available in 1.5" and 2.5" connections.

Style	AWG Product number	Fog pattern	Pistol grip	Swivel inlet	length	Weight (lbs)	GPM@100 psi
Shut off							
TT-SO 1.5"	60690733			1.5"	6.25"	3.50	
TT-SO 2.5"	60690833			2.5"	6.25"	3.50	
TT-SO 1.5" PG pistol grip	60687833		x	1.5"	6.25"	3.20	
TT-SO 2.5" PG pistol grip	60687933		x	2.5"	8.25"	4.00	
Turbo fog tip							
TT-N-30-125 MRT ST	60691033	Filled			7.50"	2.50	30-60-95-125
TT-N-30-125 ST	60691133	hollow			7.50"	2.75	30-60-95-125
TT-N-95-200 FT	60691233	Filled			9.75"	4.75	95-125-150-200
TT-N-125-250 FT	60691333	Filled			9.875"	4.75	125-150-200-250
TT-N-30-200 FT	60691433	Filled			9.875"	4.75	30-95-150-200
Additional Tips available	AWG Product number			Description	Length	weight	GPM@100 psi
TT-CAFS 1"	30012733				9.125"	1.65	
TT-CAFS 1 1/4"	60637633				5.25"	1.50	
TT-Piercing	30016645				44.00"	7.10	30
TT-FE FireEX	60662333			for light water	21.50"	7.10	20-30 GPM@75 psi
Fire-Ex Cartridge 6 pcs	60465699				10.25"	1.60	
TT-CF Container Fog	30011533			Square pattern	14.00"	2.70	70
TT-Fog Electrical	40485833			Extremely fine fog	5.25"	1.62	30
TT-ST5-42 smooth bore	60662833				3.00"	1.05	42
TT-ST5-75 smooth bore	60691533				3.125"	1.125	75
TT-ST5-170 smooth bore	60690933				5.875"	1.35	170
TT-ST5-260 smooth bore	60691633				5.875"	1.30	260
TT-ST5-300 smooth bore	60691733				5.875"	1.30	300
TT-FLS flat stream	40485933			45° flat stream	3.00"	1.00	37
TT-HFA 3% foam agent	60688033				14.50"	3.95	9 GPM@75 psi
TT-LF-60 low expansion	60661833				26.625"	3.70	60
TT-LF-95 low expansion	60692233				26.50"	3.60	95
TT-LF125 low expansion	60661933				30.75"	6.20	125
TT-HF-60 high expansion	60692333				17.75"	6.35	60
TT-HF-95 high expansion	60692433				21.50"	9.50	95
TT-HF-125 high expansion	60692533				21.50"	9.16	125
TT-SHMF-60 selectable	60688133				20.375"	10.25	60
TT-SHMF-125 selectable	60692633				22.75"	14.10	125